

# EXHIBITIONS MEDIA CENTER

## LOCATION:

112 S. Michigan Ave  
Room 106  
312.345.3622

## HOURS:

Monday - Friday  
1pm - 5pm

If you need audiovisual equipment for installation in SAIC on-campus gallery exhibitions, please fill out an **EXHIBITION REQUEST FORM** at [greenlight.artic.edu](http://greenlight.artic.edu). You will need to enter your email credentials to access the system. Use your email login and password if prompted.

For **THESIS** Exhibitions, you will be required to set up a meeting with the Exhibitions Media Center Manager one month prior to installation.

Exhibition Requests will only be approved for SAIC gallery spaces. Exhibition equipment may not be used in any off campus shows. *SAIC spaces other than the Sullivan Galleries or SUGs spaces will be considered on a case-by-case basis.*

If you have any Media Center fines, you will not be able to check out equipment from any Media Center location, including the exhibitions pool.

Any questions can be directed to the Exhibitions Media Center Manager, Audra Jacot at [ajacot@saic.edu](mailto:ajacot@saic.edu).

## VIDEO PROJECTORS

Brand/Model	Dimensions	Resolution	Lumens	Contrast	Image Size	Connectivity	Features
<b>Optoma</b> HD25-LV	12.7" x 3.8" x 9.2" 6.8 lbs	1920 x 1080 (16:9); 720p, 1080i, 1080p	3500	20,000:1	38" - 301" Throw distance: 3.9' - 32.8'	HDMI x 2, VGA- in, VGA-out, RCA	3D ready
<b>Epson</b> Powerlite 1284	11.7" x 9.6" x 3.2" 5.7 lbs	1920 x 1200 (16:10); 1080p	3200	15,000:1	30" - 300" Throw distance: 3.6' - 29.3'	HDMI x 2, VGA, RCA, USB (PC or Mac), USB (Plug 'n Play)	Wireless capabilities (from laptop, tablet, or smartphone), Can display Image and Movie (.avi) files from USB drive
<b>Canon</b> REALiS WUX450ST	13.3" x 4.6" x 16.9" 13 lbs	1920 x 1200 (16:10); 1080p	4500	2000:1	30" - 300" Throw distance: 1.2' - 11.9'	HDMI, DVI, USB (jpeg only)	Short-throw; vertical lens shift, split-screen capabilities (HDMI and DVI)
<b>Optoma</b> GT1080	12.4" x 4" x 8.8" 5.8 lbs	1920 x 1080 (16:9); 1080p	2800	25,000:1	30" - 300" Throw distance: 1.6' - 11'	HDMI x 2	3D ready; Short- Throw
<b>Panasonic</b> PT-RZ470UW HD DLP	17.9" x 4.9" x 16.3" 22.1 lbs	1920 x 1080 (16:9), 1080p	3500	20,000:1	40" Throw distance: 8.5' - 31.8'	HDMI, DVI, VGA	Laser/LED hybrid lamp; Mount horizontal or vertical, 3D ready; manual lens shift
<b>Qumi</b> Q5	1.3" x 6.3" x 4" 1.1 lbs	1280 x 800 (720p)	500	10,000:1	3.3' x 9.9'	HDMI, VGA/ Component, AV Mini-jack, Mini- jack, USB	3D capable, pocket projector; plays video off USB



Optoma HD25-LV



Canon REALiS  
(short throw)



Panasonic  
PT-RZ470  
(laser)



Epson Powerlite 1284



Optoma GT1080  
(short throw)



Qumi Q5  
(available in black and white)

There will be a **\$30 BULB USAGE FEE** for use of data/video projectors for five days or longer. This is a fee, not a deposit. You will not receive this money back again. This amount will be assessed via WebCheckout and may be paid in the same manner as a Media Center fine: by ARTICard at the Media Center. Once you take possession of the equipment, there will be no refund, even if you “never used” the projector.

## MONITORS

Type	Brand/Model	Dimensions	Resolution	Connectivity	Features
22"	<b>Samsung</b> UN22F5000AF 22-Inch LED	20.2" x 12.7" x 1.7" 5.7 lbs	1920 x 1080 (16:9)	HDMI,VGA, Component, RCA, USB	<b>NOTE: extremely limited supply</b>
32"	<b>Samsung</b> UN32D6000 32-Inch LED	30.2" x 18.7" x 1.2" 15.4 lbs	1920 x 1080 (16:9)	HDMI,VGA, Component, RCA, USB	120Hz, Ethernet & USB compatible, Wall-Mountable, SRS TruSurround Sound.Very sleek.
32"	<b>Samsung</b> UN32J5003AF 32-Inch LED	29.2" x 17.2" x 3.1" 8.4 lbs	1920 x 1080 (16:9)	HDMI, Component, RCA, USB	Very light-weight, low-profile bezel, tilting wall-mount
40"	<b>Samsung 3D</b> UN40D6400 40-Inch 3D LED	36.6" x 1.2" x 21.5" 22 lbs	1920 x 1080 (16:9)	HDMI,VGA, Component, Composite, USB	3D Capable (includes 1 pair glasses), 120Hz, Ethernet, bluetooth, & USB compatible,Wall-Mountable, SRS TruSurround Sound
40"	<b>Samsung 4K</b> UN40KU6300F 40-Inch LED	36.1" x 23.5" x 11.3" 17 lbs	3840 x 2160	HDMI x 3, Component, RCA, USB	Bluetooth capable for audio, UHD Upscaling
55"	<b>Samsung 4K</b> UN55HU850F 55-Inch LED	48.4" x 27.8" x 1.4" 39.2"	3840 x 2160 4K UHD	HDMI x 4, Component, RCA, USB	240 Motion rate, UHD Upscaling, 3D ready, Bluetooth, smart remote <b>NOTE: extremely limited supply</b>
65"	<b>Samsung 4K</b> JU7500 65-Inch LED	57.4" x 33.3" x 4.8" 58 lbs	3840 x 2160 4K UHD	HDMI x 4, Component, RCA, USB	Curved tv, 240 Motion rate, smart remote, 3D ready, UHD Upscaling <b>NOTE: extremely limited supply</b>



22" LED



40" 4K LED



32" LED



55" 4K LED



65" Curved 4K LED

Recommended file type  
for video playback:

By default, all monitors come with wall-mounts. Please specify if you'd prefer a table stand instead.

1080p

H.264

mp4

under 4GB

All monitors are capable of playing videos through their USB port.

high-quality 3.0 USB

## PLAYERS

Brand/Model	Dimensions	Playback Formats	Connectivity	Features
<b>BrightSign</b> HD222	4.9" x 1.3" x 5.4" 16.6 oz	MOV, MP4, MPG	HDMI, VGA, DVI	Seamless Repeat Playback, capability to sync multiple videos together. <b>Read opposite page for instructions.</b>
<b>WD TV Live Hub</b> Media Player USB drive	1.57" x 3.94" x 4.94" 0.67 lbs	AVI (Xvid, AVC, MPEG1/2/4), MPG/MPEG, VOB, MKV (h.264, x.264, AVC, MPEG1/2/4, VC-1), TS/TP/ M2T (MPEG1/2/4, AVC, VC-1), MP4/MOV (MPEG4, h.264), TIFF, JPEG, MP3, AIFF	Gigabit Ethernet, USB 2.0, HDMI, RCA, Component video, Optical audio	1TB on-board storage, Repeat Playback, full 1080p output, network and internet connectivity, USB compatible
<b>WD TV Live</b> Media Player USB drive	1.57" x 3.94" x 4.9" 0.67 lbs	AVI, MPG/MPEG, VOB, MKV, TS/TP/M2T, M2TS, WMV9; JPEG, GIF, TIF/ TIFF, BMP, PNG; MP3, WAV/PCM/ LPCM, WMA, AAC, FLAC, MKA, AIF/AIFF, OGG,	HDMI, Composite A/V, Component video, USB 2.0, Ethernet	Repeat Playback, full 1080p output, network and internet connectivity, USB drive compatible
<b>Sony</b> NWZ-E383 MP3 Player	1.75" x 3.5" x 0.4"	MP3, WMA, AAC-LC, Linear PCM	Audio mini out	4G, about 2,550 songs (averaging 4 minutes each), FM radio. <b>Note: Extremely limited supply</b>
<b>Panasonic</b> DMP-BDT110 3D Blu-ray Player	7.1 x 17 x 1.4 inches ; 3.5 pounds	DVD+/-R, BD-ROM, BD-R, BD-RE, BD-R DL, BD-RE DL, CD-R, DVD, CD, DVD+RW, DVD-CD-RW, DVD-RW	HDMI, Composite, component, USB 2.0, Ethernet	Repeat Playback, 3-D capable, USB playback (JPEG, MP3, MKV), SD Card Slot, Internet Streaming Capable (audio & video),



BrightSign



WD TV Live



WD TV Live Hub



Sony Mp3 Player



Panasonic Blu-ray Player

When checking out a media player, you will need to author your content appropriately. If you have never created video content before, please set enough time to learn or attend a workshop before install. We will not be able to edit your video for you.

The 8th floor McLean Media Center offers **Premiere Pro workshops** or you can check out **lynda.com**.



BrightSign players require an SD card (not provided) formatted as FAT32 or NTFS on a Windows computer or MS-DOS (FAT) or Mac OS Extended on an Apple computer. We recommend you use a reputable brand class 10 card for best results.

### **Recommended Specs:**

1080p or 720p  
60fps  
under 2GB

### **Exported as:**

H.264 (.mp4) OR  
Quicktime (.mov)

Just drag and drop your file onto the SD card. Make sure there is no other content on the card. It should play and loop automatically when the Brightsign is turned on. For anything larger than 2GB or outside of the recommended specs, please contact Audra Jacot at [ajacot@saic.edu](mailto:ajacot@saic.edu).

**\*If syncing multiple videos to loop together, please contact Audra Jacot, [ajacot@saic.edu](mailto:ajacot@saic.edu) to program your cards for you.**

### **Specs for Synced Videos:**

Same video specs as above.  
All videos MUST BE the same exact length.  
Cannot sync multiple audio files. Only ONE video can contain audio.

## COMPUTERS

Brand/Model	Dimensions	Accessories	Processor	RAM	Storage	Software
Apple 21.5" iMac	17.7" x 20.8" x 6.9" 12.5 lbs Screen 24" diagonal	Wired keyboard Wired mouse Power adapter VGA adapter Kensington lock	3060 MHz <i>Core 2 Duo</i>	4GB	500GB	Current Mac OS Standard Student Template. Admin access to install additional programs
Apple 27" iMac	20.3" x 25.6" x 8" 21 lbs Screen 27" diagonal	Same as above	2700 MHz <i>Intel Quad Core i5</i>	8GB	1 TB	Same as above
Apple Mac Mini	7.7" x 7.7" x 1.4" 2.6 lbs monitor not included	Same as above. Wall mount included	2530/2660 Mhz <i>Core 2 Duo</i>	4GB	320GB	Same as above



*21.5" iMac with table stand*



*21.5" iMac with wall mount*



*27" iMac with table stand.  
Wall mount also available*



*Mac Mini  
(w/o accessories)*



*Mac Mini  
with wall mount*

Must specify whether wall mount or table stand is preferred on iMacs.

All computers come with wired keyboard and mouse. Must request wireless mouse and keyboard if preferred.

## SPEAKERS

Brand/Model	Dimensions	Amp	Drivers	Frequency Response	Connections	Features
<b>Advent</b> AV570 Powered Speaker	6.5" x 10.5" x 7.6" 9.92 lbs	35-watt built-in amplifiers	5" Woofer; 1" Tweeters	40 to 25,000 Hz	RCA Mono	Individual bass and treble controls. No amp necessary
<b>M-Audio</b> AV40 Stereo Speaker	8.75" x 6" x 7.25" 14 lbs	20W	1" Woofer; 1" Tweeter	85 - 20,000 Hz	RCA stereo; 1/4" stereo	Comes in a pair that connect to each other with speaker wire; NOTE: extremely limited supply
<b>Bose</b> Companion 2 Stereo Speaker	7.5" x 3.1" x 5.9" 3.4 lbs	22W	One 2.5" full-range driver per speaker	Not given by the manufacturer	RCA stereo	Comes in a pair; Good for computers
<b>Kanto</b> YU3GB Powered Shelf Speakers	10.7" x 16.1" x 11.8" 14.7 lbs	30W	1" Tweeter, 4" Kevlar driver		2x Optical Audio, Bluetooth, 3.5mm mini-jack, RCA	Bluetooth capable
<b>Soundtube</b> RS 500i Open-ceiling Speaker	9.68" x 11.74" 9.5lbs	175W	1" Woofer; 1" Tweeter	61-22,000 Hz	Four-pin Euro-block	Hangs from ceiling; Open-ceiling sound
<b>PylePro</b> PCAU33 Stereo Amplifier	7.48" x 2.87" x 5.39" 4 lbs	2x75W 10% RMS at 4-ohm	N/A	N/A	RCA Stereo; Mini Stereo; USB 2.0	USB input for playback; Treble & bass control;
<b>Jamo</b> A 500 Speaker	9.8" x 11.2" x 3.0" 3.5 lbs	N/A	4" Woofer; 2" Tweeter	80 - 20,000 Hz	Speaker Wire	Flat design perfect for wall mounting; Easy installation; Descreet white color. <b>To be used with PylePro AMP.</b>
<b>Soundtube</b> fp 6020 Parabolic Speaker	8.75" x 20.25"	15W	2" x 1" aluminum, high excursion	170 Hz - 22,000Hz	Four-conductor 16-gauge hardware leads	Targeted audio footprint. <b>To be used with PylePro AMP.</b>



Advent AV570



Bose Companion 2



Soundtube RS 500i  
Open-ceiling speaker



PylePro PCAU33  
Stereo AMP (for use  
with Jamo or Parabolic)



Jamo A500  
(requires AMP)



M-Audio



Kanto YU3GB



Soundtube fp 6020  
Parabolic Speaker  
(requires AMP)

## MISCELLANEOUS

Brand/Model	Dimensions	Connections	Features
<b>Nix</b> X12B 12" Digital Photo Frame	9.2" x 12" x 3.7" 4lbs	USB, SD	800 x 600 (4:3) Back-lit LCD. Splitscreen Function; Wall-mountable, plays AVI and MP4 video at 720p
<b>Kodak</b> Ektagraphic III 35mm Slide Projector	11 x 13 x 5 in 11.75 lbs	N/A	Can be used with Timing/Dissolve unit.
<b>Logitech</b> C930e Webcam	3.7" x 1.7" x 2.8" 6 oz	USB	1080p 30fps, 90-degree field of view, 4x digital zoom, pan and tilt, ZEISS glass lens, built in mic. <b>Note: If installing live cameras in the Sullivan Galleries, you MUST clear this with security.</b>
<b>Numark</b> TT1 USB Turntable	20" x 17" x 7" 14.6 lbs	USB, RCA outputs	Records directly to iPod video (5th gen) and iPod nano (2nd gen), or directly to computer (via USB). 33 and 45 RPM belt-drive turntable



*Kodak  
Ektagraphic III*



*Nix X12B  
12" Digital Photo Frame*



*Numark TT1  
USB Turntable*



*Logitech C930e  
Webcam*